

16A4NAK – Low PIM PCS Duplexer

Renaissance Electronics has designed a new Low PIM PCS Duplexer, Model 16A4NAK. This Duplexer operates from 1850 to 1995 MHz with an 18 dB minimum isolation, PIMD 160 dBc Min @ 2x43 dBm input and 1.5 dB maximum loss.

Parameter	Specification	
	Tx	Rx
Frequency Range	1930 MHz – 1995 MHz	1850 MHz – 1915 MHz
Bandwidth		
Insertion Loss	1.5 dB Max	
Passband Ripple	-	
Return Loss	18.0 dB Min	
PIMD	160 dBc Typ @ 2x43 dBm Input	
Isolation	65 dB Min @ Rx Band	65 dB Min @ Tx Band
Average Power Rating	60W CW	
In/Out Impedance	50 Ohms	

Parameter	Specification	
	Operating	Non-Operating
Temperature	-30°C to +70°C	-55°C to +125°C
Humidity	MIL-STD-810 Method 106F	
Altitude	MIL-STD-810 Method 105C	
Mechanical Shock	MIL-STD-810 Method 213B	
Random Vibration	MIL-STD-810 Method 214	
Salt Fog	MIL-STD-810 Method 101D	
ROHS	Compliant	

Parameter	Specification
Dimension (WxDxH)	150.0 x 118.0 x 36.0 (mm) / without connector
Connector	ANT Port: N Female Connector Tx/Rx Port: N Female Connector
Finish	Black Epoxy Coating
Weight	-