

SOLID STATE SWITCH MATRIX


MODEL NUMBER:
18A2BA

Custom Applications

“Keypad Controlled”

Renaissance Electronics recently completed development of an 8 in by 12 out solid-state Switch Matrix.

The Matrix is controlled by a Keypad and/or Ethernet (it has its own TCP/IP). The ability to access and control integrated switch products is a first for Renaissance. In addition to custom programming we also incorporated new design disciplines that reduced the cabling with printed circuit solutions.



Characteristics

Frequency range:	10 – 1200 MHz
Configuration:	8 Inputs, 12 Outputs (8 x 12)
Monitoring:	One Monitoring Output for Each of the 12 Outputs
System Type:	Non-Blocking, Full Fan Out
Switching Element Technology:	Solid-State GaAs
Impedance:	50 ohms
Max Input Power:	0 dBm
Nominal Input Level Range:	-50 to 10 dBm
I/P & O/P VSWR:	< 1.3:1
Gain:	Unity
Frequency Response:	± 0.5 dB
Noise Figure:	< 12 dB
Isolation (Input to Input):	> 60 dB
Isolation (Output to Output):	> 60 dB
Isolation (Input to Output):	> 60 dB
Switching Speed:	10 ms
I/P & O/P Signal Connectors:	BNC (F)
Location of Signal Connectors:	Rear Panel
AC Power:	230 V ± 10% AC, 50 ± 3 Hz AC
Local Control Interface:	Front Panel Keypad with LCD Screen
Remote Control Interface:	Ethernet/RS-232/RS-422/IEEE-48
Mechanical:	< 3U
Operating Temperature:	-10 to 50° C



12 LANCASTER COUNTY ROAD
HARVARD, MA 01451
978-772-7774
WWW.REC-USA.COM

The New Thinking in Wireless Technology



© 2007

REC MODEL 18A2BA

Characteristics

Frequency range:	10 – 1200 MHz
Configuration:	8 Inputs, 12 Outputs (8 x 12)
Monitoring:	One Monitoring Output for Each of the 12 Outputs
System Type:	Non-Blocking, Full Fan Out
Switching Element Technology:	Solid-State GaAs
Impedance:	50 ohms
Max Input Power:	0 dBm
Nominal Input Level Range:	-50 to 10 dBm
I/P & O/P VSWR:	< 1.3:1
Gain:	Unity
Frequency Response:	± 0.5 dB
Noise Figure:	< 12 dB
Isolation (Input to Input):	> 60 dB
Isolation (Output to Output):	> 60 dB
Isolation (Input to Output):	> 60 dB
Switching Speed:	10 ms
I/P & O/P Signal Connectors:	BNC (F)
Location of Signal Connectors:	Rear Panel
AC Power:	230 V ± 10% AC, 50 ± 3 Hz AC
Local Control Interface:	Front Panel Keypad with LCD Screen
Remote Control Interface:	Ethernet/RS-232/RS-422/IEEE-48
Mechanical:	< 3U
Operating Temperature:	-10 to 50° C

WWW.REC-USA.COM

The New Thinking in Wireless Technology