

Micro-Strip Circulator

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER WATTS	MODEL #
2.300 - 2.700	20	0.400	1.250:1	2	3W4NH
2.500 - 2.900	20	0.400	1.250:1	2	3W4NJ
3.600 - 4.200	20	0.400	1.250:1	2	3W5NH
5.900 - 6.450	20	0.500	1.250:1	2	3W7NH
7.200 - 8.200	20	0.500	1.250:1	2	3W7NJ
8.500 - 9.600	20	0.500	1.250:1	2	3W8NK
9.600 - 14.400	20	0.500	1.250:1	2	3W8BJ
10.000 - 11.000	20	0.500	1.250:1	2	3W8NM
10.950 - 11.700	20	0.500	1.250:1	2	3W9NG
11.000 - 12.500	18	0.600	1.300:1	2	3W8NJ
12.000 - 13.500	18	0.600	1.300:1	2	3W9NJ
12.400 - 13.000	20	0.500	1.250:1	2	3W9NH
14.000 - 14.500	18	0.600	1.300:1	2	3W9NM
14.500 - 15.500	18	0.600	1.300:1	2	3W9NK
17.700 - 19.700	17	0.800	1.300:1	2	3W9NN
21.200 - 23.600	17	0.900	1.300:1	2	3W9NP
24.250 - 26.750	20	0.900	1.300:1	2	3W9NV
27.350 - 31.700	20	0.900	1.300:1	2	3W9NW
34.000 - 36.000	20	0.900	1.300:1	2	3W9NT
37.000 - 39.500	20	0.900	1.300:1	2	3W9NR

TYPICAL PACKAGE DIMENSIONS

