

BROADBAND COAXIAL CIRCULATORS

COAXIAL CIRCULATORS

FREQUENCY GHz	ISOLATION dB, MIN	INSERTION LOSS dB, MAX	VSWR MAX	POWER WATTS	MODEL #	DIMENSIONS IN INCHES
0.225 - 0.400	16	0.900	1.400:1	40	3A2BA	2.580 X 2.050 X 1.140
1.000 - 2.000	18	0.600	1.350:1	50	3A3BR	2.600 X 2.000 X 0.750
1.350 - 2.700	14	0.700	1.500:1	50	3A4BF	2.600 X 2.600 X 0.750
2.000 - 4.000	18	0.500	1.300:1	100	3A5BA	1.250 X 1.250 X 0.500
2.600 - 5.200	18	0.500	1.300:1	50	3A5BH	1.250 X 1.250 X 0.700
3.000 - 6.000	17	0.500	1.350:1	50	3A6BF	1.250 X 1.250 X 0.700
4.000 - 8.000	18	0.500	1.300:1	50	3A7BF	1.000 X 1.130 X 0.500
5.000 - 10.000	18	0.500	1.300:1	60	3A7BG	0.750 X 0.750 X 0.500
6.000 - 12.000	18	0.600	1.300:1	60	3A8BW	0.750 X 0.750 X 0.500
6.500 - 16.500	14	0.750	1.500:1	80	3A8BI	0.500 X 0.620 X 0.500
12.000 - 18.000	20	0.500	1.250:1	65	3A9BK	0.500 X 0.620 X 0.500

TYPICAL PACKAGE DIMENSIONS



