

Datasheet

Description

Farran Technology offers the WGNS series of noise sources to be used in conjunction with the FBC down converters for use as frequency extenders for noise figure measurement test system. The WGNS-XX is a fullband noise source. The WGNS-15 covers the full W band 50 – 75 GHz.



Features

- Full waveguide band
- High ENR
- Uniform level of noise power spectral density
- Compatible with Agilent NFA
- Compatible with Agilent PXA with noise figure personality
- Convenient packing to match the VNA frequency extension

Applications

- Frequency extenders for noise figure measurement systems
- Communications
- OEM test instrumentation
- EW and ECM systems
- Radar front ends

Specification	Unit	Min	Тур	Max
System Operating Frequency	GHz	50		75
ENR	dB		12.5	
Trigger Voltage	V		+28	
Pause between triggering pulses	ms	0.5		
VSWR				1.4:1
	·			
Test Port Interface	-	WR-15 UG-385/U		
Trigger connector	-	BNC (F)		
Power Requirements	-	240/110 V AC		
Weight	kg		3.5	
Dimensions (L x W x H)	-	200 x 120 x 90		




Sold and supported in the USA by HXI, LLC sales@hxi.com 978-772-7774




Page 1 of 2



Datasheet







Sold and supported in the USA by HXI, LLC sales@hxi.com 978-772-7774



Page 2 of 2