



HLS 7451

## HXI Gigalink LightSpeed™ 7451

- Speed of light latency
- High-Performance 1.25Gbps E-Band Radio Link
- For Light-licensed deployment
- Highest power with lowest latency in the industry

Millimeter Wave Performance	HLS 7451 Specifications
Frequency	71.0 to 76.0 GHz
RF Injection Power into Antenna	-1 version +17 to +20 dBm -2 version +20 to +23 dBm -3 version +23 to +26 dBm
Receive Sensitivity 10 <sup>-6</sup> BER	-62 dBm
Latency Back to Back	4 nanoseconds
Antenna Type	12-in. parabolic, Slip Fit Clip On
Antenna Gain	44 dBi
3-dB Beam Width	0.80 degree
Interfaces	
Payload Interface	Gigabit Ethernet, 1000Base-SX, 850 nm, FC connector
Management	RG-45
Installation	10/100 BaseT, RJ-45 modular jack
Power	MIL-C-5015-type connector for 12- to 16-AWG three-conductor power cable
Management	
Installation Tools	Built-in web browser-based GUI and SNMP agent
Remote Monitoring	via SNMP or Web browser-based GUI, self-contained in radio

\*All specifications are subject to change without notice



HLS 7451



HLS 7451

Regulatory Compliance	
Electrical	UL - UL60950, EN-60950-1, IEC 609050-1
EMC	EN 55022, Emissions Class A, EN 301 489 Immunity
Laser Safety	CDRH - Class 1 (21 CFR 1040 per Laser Notice No. 50)
Power	
Input Voltage	-48 VDC nominal (-40 to -57 VDC)
Power Consumption	70W Max. 40W operating typical
Maximum Input Current	1.5 Amps maximum at turn on, heaters for cold start
Environmental & Mechanical	
Operating Temperature	-30°C to 60°C (-22°F to 140°F)
Storage Temperature	-30°C to 85°C (-22°F to 185°F)
Relative Humidity	Up to 95%, non-condensing
Transceiver H x W x D	13 x 13 x 14.7 in. (33 x 33 x 37.3 cm)
Transceiver Weight	18 lbs (8 kg) including antenna and mount

**OPTIONS**

- AC-DC outdoor rated power supply
- Sighting scope, Picatinny rail attached to two foot antenna
- Payload: 1000 Base LX FC connector, special order
- One and two foot antennas in any combination
- Dual polarization dual radio adaptor for one and two foot antennas

**HXI Gigalink™ 7451 Specifications**

- Range Performance: Please specify location and we will assist with range calculations for required availability